



iTac Clear

An optically clear PET film backed with a proprietary adhesive for interior and exterior applications on a variety of smooth surfaces.

iTac Clear is the perfect choice to communicate your branding and messaging with crisp color.

The proprietary adhesive technology supports a wet or dry install for flawless graphics and long-term removal without residue.

APPLICATIONS

- Retail and Decorative Window Graphics
- Corporate Environmental Graphics
- High-Quality Labeling for Electronics, Glass, and any Smooth Surface

iTac Clear

MATERIAL

Face Film	Optically Clear Gloss PET
Back Side	Clear Adhesive
Adhesive	Proprietary Removable Repositionable Rinsible
Liner	Siliconized Frosted PET
Total Thickness	4.3 mil (110µ +/-10µ)
FR Certification	Not Tested
Recyclable	Yes, Where Facilities Allow

DURABILITY

Interior	Up to 3 Years - Vertical Exposure under Normal Conditions, Exclusive of Ink
Exterior	Up To 2 Years - Vertical Exposure under North American Midwestern Conditions, Exclusive of Ink
Environment	Humidity & Solvent Resistance - Very Good
Shelf Life	1 Year
Storage Requirements	Store at +50°F to +75°F (+10°C to +24°C) and Relative Humidity Between 45% and 60%
Repositionable	Yes

APPLICATION/REMOVAL

Application Temp	Minimum +25°F (-4°C)
Service Temp	+0°F to +250°F (-17°C to +121°C)
Removability	Cleanly Removable up to 3 Years
Removal Temp	+50°F (+10°C) or Greater

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean glass or install surface with a mild detergent and water and dry thoroughly prior to application. May be wet installed. For full installation and removal recommendations, please refer to "iTac Clear Handling Recommendations".

**For critical substrates and all surfaces, please test PRIOR to application.*

Rev 10/2025



Printing Methods

- Digital - UV & Latex (Gen 3+); Screen Print



Material Sizes

- iTac Clear: 54" x 100'



Advantages

- Easy Application on a Variety of Smooth Surfaces
- PVC-Free Construction and Recyclable Where Allowed
- Proprietary Adhesive offers Clean Removal Even After Long-Term Installation
- Extremely Dimensionally Stable

→ For more information

For additional product information, performance, and warranty guidelines please contact Continental Grapix USA, Inc.

704-872-2216 • www.cgxusa.com