



iTac White

A white matte PET film backed with a proprietary hybrid adhesive for interior and exterior applications on glass and other smooth surfaces.

Spotlight your branding and messaging with luminous graphics day into night.

Proprietary adhesive technology supports dry and wet installation on glass for bubble-free results and long-term, residue-free removal.

APPLICATIONS

- Retail and Decorative Window Graphics
- Corporate Environmental Graphics
- High Quality Labeling for Electronics, Glass, LCD Screens
- Any Smooth Surface

iTac White

MATERIAL

Face Film	Matte White PET
Whiteness	91 +/- 1 (ASTM E313)
Back Side	Clear Adhesive
Adhesive	Proprietary Repositionable Removable Rinsible
Liner	Siliconized Frosted PET
Total Thickness	4.5 mil (115µ +/- 10µ)
FR Certification	Not Tested
Recyclable	Yes - Where Facilities Allow

DURABILITY

Interior	Up to 3 Years - Vertical Exposure under Normal North American Midwestern Conditions, Exclusive of Ink
Exterior	Up to 2 Years - Vertical Exposure under Normal North American Midwestern Conditions, Exclusive of Ink
Environment	Humidity & Solvent Resistance - Very Good
Shelf Life	1 Year
Storage Requirements	Store at +50°F to +75°F (+10°C to +24°C) and Relative Humidity Between 45% and 60%
Repositionable	Yes

APPLICATION/REMOVAL

Application Temp	Minimum +25°F (-4°C)
Service Temp	+0°F to 250°F (-17°C to +121°C)
Removability	Cleanly Removable up to 3 Years
Removal Temp	+50°F (+10°C) or Greater

**Smooth surface must be clean and dry. Prevent contact with solvents or ammonia-based cleaners. For best results, clean installation surface with soap and water ONLY. Rinse with water and dry after cleaning. ALWAYS clean and dry glass surface prior application. For full installation and removal recommendations, please refer to "iTac Clear and iTac White Handling Recommendations".*

For critical substrates and all surfaces, please test PRIOR to application.



Printing Methods

- Digital - Solvent, Eco-Solvent, Latex & UV



Material Sizes

- 54" x 100'



Advantages

- Easy Application on a Variety of Smooth Surfaces
- Proprietary Hybrid Adhesive Offers Ability to Install in Cold Temperatures as well as Long-Term Clean Removability
- PVC-Free Construction and Recyclable Where Allowed
- Long-Term Dimensional Stability



For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

704-872-2216 • www.cgxusa.com