



ProtectWalk

A calendared, embossed, printable, pressure-sensitive overlamine film.

Specially developed for floor graphic applications where slip resistance is mandatory.

Excellent frosted printable film for window graphics.

ProtectWalk can add body and extend the life of any graphic.

APPLICATIONS

- Apply Over X-Treme to Create Removable Reusable Floor Graphics
- Non-Slip Laminate for Event Graphics, Reception Areas, Shops, and Office Buildings
- For All Floor Graphic Applications

ProtectWalk

MATERIAL

Face Film	Textured PVC
Back Side	Clear
Adhesive	Clear Permanent Solvent - 20g/m ² +/- 3g/m ²
Liner	Siliconized Paper
Film Thickness	7 mil (180µ +/- 5 µ)
FR Certification	Not Tested
Slip Resistance	ANSI A137.1/A326.3, R10

DURABILITY

Interior	Up to 1 year
Exterior	N/A
Environment	Humidity & Solvent Resistance – Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 77°F (+15°C to +25°C) and Relative Humidity between 40% to 65%
Repositionable	No

APPLICATION/REMOVAL

Application Temp	Minimum +50°F (+10°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removal Temp	Minimum +50°F (+10°C)
Laminating Method	Cold, Heat Assist

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best installation results, clean surface with a mild detergent and water and dry thoroughly. Printed material must be completely dry and/or off-gassed prior to lamination. For best results, use as little laminator tension as possible to avoid film stretching.

**For critical substrates and all surfaces, please test PRIOR to application.
Rev 10/2026*



Printing Methods

- Digital – Solvent, Eco-Solvent, UV, & Latex



Material Sizes

- 54" x 150'
- 54" x 50'



Advantages

- Provides Required Slip-Resistance for Printed Floor Graphics
- Create Clear, Printable, Non-Skid Floor Graphics
- Siliconized Paper Liner for Easier Handling

→ For more information

For additional product information, performance, and warranty guidelines please contact Continental Graftix USA, Inc.

704-872-2216 • www.cgxusa.com